

COUPLING/DECOUPLING NETWORK



FCC-801-M2-50A

Specifications

Application: IEC 61000-4-6 Conducted Immunity
Frequency: 150 kHz – 230 MHz
Supply Lines: 2 Power Conductors
Impedance: Frequency dependent
150 kHz – 26 MHz: $150 \Omega \pm 20 \Omega$
26 MHz – 80 MHz: $150 \Omega +60 \Omega - 45 \Omega$
Published IEC 61000-4-6, Table 3
80 MHz – 230 MHz $150 \Omega +60 \Omega - 60 \Omega$
Published IEC 61000-4-6, Annex B Table B.1

Maximum Current: 50 A
Maximum Voltage: DC - 60 Hz, 250 V line to ground maximum
480 V line to line maximum

RF Disturbance Port:
Power Rating: 12 Watts max
EUT/Mains Connector: 6 mm Multi-Contact Safety Socket
RF Disturbance Port: 50 Ω BNC
Dimensions (L x W x H): 23 cm x 15 cm x 13 cm
Weight: 2.4 kg



Fischer Custom Communications, Inc.

19220 Normandie Ave., Unit B Torrance, CA 90502
Phone: 310-303-3300

Email: sales@fischercc.com

© Fischer Custom Communications, Inc.