

COUPLING/DECOUPLING NETWORK

FCC-801-S37



Specifications

Application:	IEC 61000-4-6 Conducted Immunity
Frequency:	150 kHz – 230 MHz
Input/Output Lines:	37
Impedance:	Frequency dependent 150 kHz – 26 MHz: $150\ \Omega \pm 20\ \Omega$ 26 MHz – 80 MHz: $150\ \Omega + 60\ \Omega - 45\ \Omega$ Published IEC 61000-4-6, Table 3 80 MHz – 230 MHz $150\ \Omega + 60\ \Omega - 60\ \Omega$ Published IEC 61000-4-6, Annex B Table B.1
Maximum Current:	3A
Maximum Voltage:	250 VAC 250 VDC
RF Disturbance Port:	
Power Rating:	9 Watts max
EUT/AE Port Connector:	D-Sub 37 Pin (Active Pins 1-37)
RF Disturbance Port:	50 Ω BNC
Dimensions (L x W x H):	23 cm x 15 cm x 13 cm
Weight:	2.0 kg



Fischer Custom Communications, Inc.

19220 Normandie Ave., Unit B Torrance, CA 90502
Phone: 310-303-3300

Email: sales@fischercc.com

© Fischer Custom Communications, Inc.